Product data sheet





Cordless Rotary Hammer with SDS plus

GBH 18V-22



Evolve, with our most compact and ergonomic Boschhammer

The most important data

Battery voltage	18.0 V
Drilling dia. in concrete with hammer drill bits	4 – 22 mm
Impact rate at rated speed	0 – 4,675 bpm

Part Number 0 611 924 001

Technical data

Technical data

Impact rate at rated speed	0 – 4,675 bpm
Rated speed	0 – 1,050 rpm
Battery voltage	18.0 V
Weight excl. battery	2.3 kg
Tool holder	SDS plus
Packaging dimensions (width x length x height)	360 x 445 x 150 mm
Impact energy nominal	1.9 J

Drilling range

Drilling dia. in concrete with hammer drill bits	4 – 22 mm
Opt. app. range in concrete with hammer drill bits	4 – 12 mm

Noise/vibration information

Hammer drilling in concrete

Vibration emission value ah	14 m/s ²
Uncertainty K	1.5 m/s ²
Chiselling in concrete	
Vibration emission value ah	9.4 m/s ²
Uncertainty K	1.5 m/s ²

Invented for life

Product data sheet

Power tools for trade & industry

Advantages:

- More holes per charge and continuous power output thanks to motor with constant speed
- Better drilling experience due to Vibration Control, designed to absorb pulsation
- Enhanced safety against accidental jams thanks to KickBack Control
- Dust-free work condition with Auto Power GDE 18V-12 / GDE 12 extractor attachment























