Product data sheet





Cordless Rotary Hammer with SDS plus

GBH 18V-26 D



Universal D-handle rotary hammer for vertical drilling and chiselling applications in the SDS plus cordless category

The most important data

·	
Battery voltage	18.0 V
Impact energy	2.5 J
Drilling dia. in concrete with hammer drill bits	4 – 26 mm

Part Number 0 611 916 000

Technical data

Technical data

Impact energy	2.5 J
Impact rate at rated speed	0 – 4,350 bpm
Rated speed	0 – 980 rpm
Battery voltage	18.0 V
Weight excl. battery	2.6 kg
Tool holder	SDS plus
Packaging dimensions (width x length x height)	288 x 573 x 114 mm
Drilling range	

Drilling dia. in concrete with hammer drill bits	4 – 26 mm
Opt. app. range in concrete with hammer drill bits	8 – 16 mm

Noise/vibration information

Hammer drilling in concrete

Vibration emission value ah	16.7 m/s ²
Uncertainty K	1.5 m/s ²
Chiselling in concrete	
Vibration emission value ah	10.9 m/s²
Uncertainty K	1.5 m/s ²

Invented for life

Product data sheet

Power tools for trade & industry

Advantages:

- Comfortable handling due to large switch and D-handle, supported by bright LED light for effortless chiselling
- First D-handle cordless rotary hammer with KickBack Control offers both flexible handling and increased user protection
- Impact energy of 2.5 J and brushless motor: cordless power equal to the corded power of established Boschhammers



























