Product data sheet





Cordless Rotary Hammer with SDS plus

GBH 18V-26



Universal rotary hammer in the SDS plus cordless category

The most important data

Battery voltage	18.0 V
Impact energy	2.6 J
Drilling dia. in concrete with hammer drill bits	4 – 26 mm

Part Number 0 611 909 001

Technical data

Technical data

Impact energy	2.6 J
Impact rate at rated speed	0 - 4,350 bpm
Rated speed	0 - 980 rpm
Battery voltage	18.0 V
Weight excl. battery	2.9 kg
Tool holder	SDS plus
Packaging dimensions (width x length x height)	363 x 152 x 446 mm
Impact energy nominal	2.6 J

Drilling range

Drilling dia. in concrete with hammer drill bits	4 – 26 mm
Opt. app. range in concrete with hammer drill bits	8 – 16 mm

Noise/vibration information

Hammer drilling in concrete

Vibration emission value ah	15.2 m/s ²
Uncertainty K	1.5 m/s²
Chiselling in concrete	
Vibration emission value ah	9.9 m/s²
Uncertainty K	1.5 m/s ²

Invented for life

Product data sheet

Power tools for trade & industry

Advantages:

- Delivers 2.6 J of impact energy for fast drilling and high chisel removal performance
- KickBack Control and Electronic Precision Control for better tool handling and increased user protection
- Optional GDE 18V-16 Professional dust extraction unit integrates with the hammer for a self-contained HEPA dust solution



























