



Product data sheet

Power tools for trade & industry

Cordless Rotary Hammer BITURBO with SDS max

GBH 18V-45 C



Cordless freedom with corded performance – the heavy-duty all-rounder for concrete drilling and chiselling up to 45 mm

The most important data

Battery voltage	18.0 V
Impact energy	12.5 J
Drilling dia. in concrete with hammer drill bits	12 – 45 mm

Part Number 0 611 913 000

Technical data

Technical data

Impact energy	12.5 J
Impact rate at rated speed	0 – 2,740 bpm
Rated speed	0 – 300 rpm
Battery voltage	18.0 V
Weight excl. battery	8 kg
Tool holder	SDS max
Packaging dimensions (width x length x height)	411 x 618 x 149 mm
Impact energy nominal	12.5 J
Battery capacity	12 Ah

Drilling range

Drilling dia. in concrete with hammer drill bits	12 – 45 mm
Opt. app. range in concrete with hammer drill bits	20 – 40 mm

Noise/vibration information

Hammer drilling in concrete

Vibration emission value ah	12.3 m/s ²
Uncertainty K	1.5 m/s ²

Chiselling in concrete

Vibration emission value ah	7.3 m/s ²
Uncertainty K	1.5 m/s ²

**BOSCH**

Invented for life

Product data sheet

Power tools for trade & industry

Advantages:

- Cordless freedom with corded performance
- KickBack Control for reduced hazard of sudden tool reactions and Soft Start EPC & ASC for a comfortable and precise work process
- Lighter than comparable corded products thanks to a highly optimized drive train

BITURBO
BRUSHLESS

AMP Share
BOSCH

