



Product data sheet

Power tools for trade & industry

Combi Laser

GCL 2-15 G



Green laser lines for up to four times better visibility

The most important data

Working range with receiver	10 m
Working range, value	15 m
Accuracy	± 0.3 mm/m

Part Number 0 601 066 J00

Technical data

Technical data

Laser diode	Line: 500 – 540 nm, < 10 mW, Point: 630 – 650, < 1 mW
Operating temperature	-10 – 50 °C
Storage temperature	-20 – 70 °C
Laser class	2
Working range, value	15 m
Working range with receiver	10 m
Accuracy	± 0.3 mm/m
Working range of laser points, max.	10 m (top), 10 m (bottom)
Self-levelling range	± 4°
Levelling time	4 s
Dust and splash protection	IP 54
Power supply	3 x 1.5 V LR6 (AA)
Operating time (max.)	6 h in cross line and point mode, 8 h in cross line mode, 10 h in line and point mode, 12 h in line mode, 22 h in point mode
Tripod thread	1/4", 5/8"
Weight, approx.	0.49 kg
Colour of laser line	green
Projection	2 lines / 2 points

Plumb point accuracy	± 0.7 mm/m
----------------------	------------

**BOSCH**

Invented for life

Product data sheet

Power tools for trade & industry

Advantages:

- Green horizontal and vertical laser lines for up to four times better visibility than red lines
- Precise transfer applications thanks to red plumb points
- Rotating mount RM 1 Professional allows laser lines to be easily aligned around the plumb points

