

**BOSCH**

Invented for life

Product data sheet

Power tools for trade & industry

Combi Laser

GCL 2-50 C



Smart functions for maximum productivity

The most important data

| | |
|-----------------------------|------------|
| Working range with receiver | 50 m |
| Working range, value | 20 m |
| Accuracy | ± 0.3 mm/m |

Part Number 0 601 066 G00

Technical data

Technical data

| | | | |
|-------------------------------------|---|----------------------------|--------------------|
| Battery voltage | 12.0 V | Weight, approx. | 0.6 kg |
| Laser diode | 635 – 650 nm | Colour of laser line | red |
| Operating temperature | -10 – 50 °C | Color of plumb points | red |
| Storage temperature | -20 – 70 °C | Projection | 2 lines / 2 points |
| Laser class | 2 | Plumb point accuracy | ± 0.7 mm/m |
| Working range, value | 20 m | Compatible laser receivers | LR 6 + 7 |
| Working range with receiver | 50 m | | |
| Accuracy | ± 0.3 mm/m | | |
| Working range of laser points, max. | 10 m (top), 10 m (bottom) | | |
| Self-levelling range | ± 4° | | |
| Dust and splash protection | IP54 (except for the battery or battery adapter) | | |
| Power supply | 12 V Li-ion or 4 x 1.5 V LR6 (AA) | | |
| Operating time (max.) | 18 h (Li-Ion) and 10 h (4 x AA) in cross-line and point operation, 25 h (Li-Ion) and 16 h (4 x AA) in cross-line operation, 35 h (Li-Ion) and 28 h (4 x AA) in line operation, 60 h (Li-Ion) and 32 h (4 x AA) in point operation | | |

**BOSCH**

Invented for life

Product data sheet

Power tools for trade & industry

Advantages:

- Bluetooth®-connection paired with Levelling Remote App offers remote-control adjustment of the tool via a smartphone
- Dual Power Source allows for a 12 V-Li-ion battery or standard alkaline batteries for increased flexibility
- Precise alignment of laser lines around centred plumb points with the manual RM 2 or motorised RM 3

