



Product data sheet

Power tools for trade & industry

Cordless Impact Driver/Wrench

GDS 18V-320 C



Compact and lightweight 3/8" impact wrench with adjustable modes for multi-purpose use

The most important data

Battery voltage	18.0 V
Torque, max.	320 Nm
No-load speed	0-1,200 rpm

Part Number 0 601 9L5 100

Technical data

Technical data

Torque adjustment range, min./max., 1st level	0/180 Nm
Torque adjustment range, min./max., 2nd level	0/220 Nm
Torque adjustment range, min./max., 3rd level	0/320 Nm
No-load speed	0-1,200 rpm
No-load speed (1st level)	0-1,200 rpm
No-load speed (2nd level)	0-1,900 rpm
No-load speed (3rd level)	0-2,800 rpm
Weight excl. battery	1.2 kg
Torque, max.	320 Nm
Impact rate	0-3,800 bpm
Impact rate (1st level)	0-2,400 bpm
Impact rate (2nd level)	0-3,100 bpm
Impact rate (3rd level)	0-3,800 bpm
Battery voltage	18.0 V
Tool holder	3/8" Square
Breakaway torque, max.	540 Nm
Packaging dimensions (width x length x height)	224 x 234 x 94 mm
BITURBO	No

Noise/vibration information

Tightening screws and nuts of maximum permitted size

Vibration emission value ah	13 m/s ²
Uncertainty K	1.5 m/s ²

**BOSCH**

Invented for life

Product data sheet

Power tools for trade & industry

Advantages:

- Two default screw modes for multi-purpose use. Each mode can be adjusted and individualised via the Bosch Toolbox App
- Powerful 320 Nm tightening and 540 Nm breakaway torque performance
- Versatile three-speed/torque settings for more flexibility and control

