



# Product data sheet

## Power tools for trade & industry

Cordless Impact Wrench

## GDS 18V-330 HC



Compact and lightweight impact wrench with adjustable modes for multi-purpose use

### The most important data

Battery voltage	18.0 V
Torque, max.	330 Nm
No-load speed	0-2,800 rpm

**Part Number** 0 601 9L5 001

## Technical data

### Technical data

Torque adjustment range, min./max., 1st level	0/200 Nm
Torque adjustment range, min./max., 2nd level	0/260 Nm
Torque adjustment range, min./max., 3rd level	0/330 Nm
No-load speed	0-2,800 rpm
No-load speed (1st level)	0-1,200 rpm
No-load speed (2nd level)	0-1,900 rpm
No-load speed (3rd level)	0-2,800 rpm
Weight excl. battery	1.2 kg
Torque, max.	330 Nm
Impact rate	2,800 bpm
Impact rate (1st level)	0-2,400 bpm
Impact rate (2nd level)	0-3,100 bpm
Impact rate (3rd level)	0-3,800 bpm
Battery voltage	18.0 V
Tool holder	1/2" square friction ring and thru hole
Breakaway torque, max.	560 Nm
Packaging dimensions (width x length x height)	360 x 440 x 155 mm

## Noise/vibration information

### Tightening screws and nuts of maximum permitted size

Vibration emission value ah	13 m/s <sup>2</sup>
Uncertainty K	1.5 m/s <sup>2</sup>

**BOSCH**

Invented for life

# Product data sheet

Power tools for trade & industry

## Advantages:

- Two default screw modes for multi-purpose use. Each mode can be adjusted and individualised via the Bosch Toolbox App
- Powerful 330 Nm tightening and 560 Nm breakaway torque performance
- Versatile three-speed/torque settings for more flexibility and control

