



Product data sheet

Power tools for trade & industry

Cordless Impact Driver/Wrench

GDX 18V-210 C



Prevents damage before it occurs – impact driver with 2-in-1 tool holder

The most important data

Battery voltage	18.0 V
Torque, max.	210 Nm
No-load speed	0-3,400 rpm

Part Number 0 601 9J0 201

Technical data

Technical data

Torque adjustment range, min./max., 1st level	0/130 Nm
Torque adjustment range, min./max., 2nd level	0/160 Nm
Torque adjustment range, min./max., 3rd level	0/210 Nm
No-load speed	0-3,400 rpm
No-load speed (1st level)	0-1,100 rpm
No-load speed (2nd level)	0-2,300 rpm
No-load speed (3rd level)	0-3,400 rpm
Torque settings	3
Weight excl. battery	1.2 kg
Torque, max.	210 Nm
Impact rate	0-4,100 bpm
Impact rate (1st level)	0-2,200 bpm
Impact rate (2nd level)	0-3,100 bpm
Impact rate (3rd level)	0-4,100 bpm
Battery voltage	18.0 V
Tool holder	1/4" Hex Uni, 1/2" Square
Breakaway torque, max.	370 Nm
Packaging dimensions (width x length x height)	360 x 444 x 155 mm

Noise/vibration information

Tightening screws and nuts of maximum permitted size

Vibration emission value ah	9.8 m/s ²
Uncertainty K	1.5 m/s ²

**BOSCH**

Invented for life

Product data sheet

Power tools for trade & industry

Advantages:

- 2-in-1 tool holder with 1/4" internal hex and 1/2" square drive for highest flexibility and broadest application
- Convenient three speed/torque settings for superior power control
- User interface with two default modes, selftapping and wood screw.

