## Product data sheet





Cordless Random Orbit Sander

GEX 18V-150-3



Optimal control for higher removal rates

The most important data

| Sanding pad diameter | 150 mm         |
|----------------------|----------------|
| Orbit diameter       | 3 mm           |
| No-load speed        | 5,000 - 10,000 |
|                      | rpm            |

Part Number 0 601 372 903

### Technical data

#### Technical data

| Sanding pad diameter                           | 150 mm                 |
|--|------------------------|
| No-load speed                                  | 5,000 - 10,000 rpm     |
| Orbital stroke rate                            | 10,000 - 20,000<br>opm |
| Eccentricity                                   | 1.5 mm                 |
| Weight excl. battery                           | 1.2 kg                 |
| Orbit diameter                                 | 3 mm                   |
| Packaging dimensions (width x length x height) | 360 x 444 x 177 mm     |
| Battery voltage                                | 18.0 V                 |
| BITURBO  | No                     |
|  |                        |

# Noise/vibration information

#### Sanding solid wood

| Vibration emission value ah | 2.5 m/s <sup>2</sup> |
|-----------------------------|----------------------|
| Uncertainty K               | 1.5 m/s <sup>2</sup> |

# Invented for life

## Product data sheet

#### Power tools for trade & industry

## Advantages:

- Excellent ergonomics of the gripping area and most compact tool height for superior tool control
- High removal rates made possible by brushless motor and 3 mm orbit
- Easy and intuitive operation due to HMI and innovative dust box with integrated Click&Clean interface











