



Product data sheet

Power tools for trade & industry

Cordless Plunge Saw BITURBO

GKT 18V-52 GC



Corded performance and superior compactness in the Bosch 18 V category

The most important data

Battery voltage	18.0 V
Saw blade diameter	140 mm
No-load speed	2,800 – 5,500 rpm

Part Number 0 601 6B4 000

Technical data

Technical data

No-load speed	2,800 – 5,500 rpm
Weight excl. battery	4.1 kg
Saw blade bore diameter	20 mm
Saw blade diameter	140 mm
Baseplate	305 x 169 mm
Bevel angle	-1 - 47 °
Packaging dimensions (width x length x height)	360 x 444 x 254 mm
Battery voltage	18.0 V
Cutting depth without guide rail (90°)	52 mm
Cutting depth with guide rail (90°)	46 mm
Cutting depth without guide rail (45°)	32 mm
Cutting depth with guide rail (45°)	32 mm

**BOSCH**

Invented for life

Product data sheet

Power tools for trade & industry

Advantages:

- BITURBO Brushless technology and ProCORE18V for maximum cordless cutting performance equal to corded 1,620 W plunge saws
- Superior mobility due to a uniquely compact design allowing operation with only one battery
- Very compact design enables minimum distance between saw blade and wall of only 10 mm

