



# Product data sheet

Power tools for trade & industry

Line Laser

## GLL 80-33 G



Easier alignment with our intuitive line laser

### The most important data

Working range with receiver	80 m (radius)
Working range, value	30 m
Accuracy	± 0.3 mm/m

**Part Number** 0 601 065 501

## Technical data

### Technical data

Battery voltage	3.7 V
Laser diode	500 – 540 nm, < 10 mW
Operating temperature	-10 – 40 °C
Storage temperature	-20 – 70 °C
Laser class	2
Working range, value	30 m
Working range with receiver	80 m (radius)
Accuracy	± 0.3 mm/m
Self-levelling range	± 4°
Levelling time	4 s
Dust and splash protection	IP 65
Power supply	4 x 1.5 V LR6 (AA), 3.7 V Li-Ion battery (3000 mAh)
Operating time (max.)	5 h (Li-Ion) and 5 h (4 x AA) in 3-line mode
Tripod thread	1/4", 5/8"
Weight, approx.	0.93 kg
Colour of laser line	green
Projection	3 x 360° line
Compatible laser receivers	LR 7

**BOSCH**

Invented for life

# Product data sheet

Power tools for trade & industry

## Advantages:

- Rubber-enforced housing and IP65 rating for dust and water resistance
- New keypad design for clear laser line selection and energy saving mode for longer battery runtime
- Dual power source for seamless switch between BA 3.7V 3.0Ah XL Li-Ion battery and AA alkaline batteries to help eliminate downtime

**PROTECTED TOOLS**  
Impact | Water | Dust