Product data sheet





Laser Measure

GLM 50-22



Laser measuring for rough job sites and easily adjustable to individual needs

The most important data

Measurement range	0.050 - 50.000 m
- Wedsdrennent range	0.000 00.000 111
Laser diode	635 nm, < 1 mW
Weight, approx.	0.2 kg

Part Number 0 601 072 S00

Technical data

Technical data

Laser diode	635 nm, < 1 mW
Measurement range	0.050 – 50.000 m
Laser class	2
Measurement accuracy, typical	± 1.5 mm
Measurement time, typical	0.5 s
Measurement time, max.	4 s
Power supply	2 x 1.5 V LR6 (AA)
Automatic deactivation	5 min
Weight, approx.	0.2 kg
Units of measurement	m/cm/mm/ft/inch/ ft-inch
Memory capacity (values)	10
Dust and splash protection	IP 65
Tripod thread	1/4"
Laser colour	Red

Invented for life

Product data sheet

Power tools for trade & industry

Advantages:

- Ideal for rough construction sites thanks to IP65 certification, shock-absorbing housing, and 1.5-m drop resistance
- Customisable favourite button for preferred measurement functions or settings
- Intuitive user interface with a Big Numbers Mode for better readability, supporting 30 languages and a new help function

















