Product data sheet





Cordless Combi

GSB 18V-110 C



Extremely powerful and robust 18 V impact drill driver with brushless motor and impact drilling function

The most important data

Torque (soft/hard/max.)	47/85/110 Nm
No-load speed (1st gear / 2nd gear)	0 - 480 / 0 - 2,100 rpm
Battery voltage	18.0 V

Part Number 0 601 9G0 30A

Technical data

Technical data

Torque (soft/hard/max.)	47/85/110 Nm
No-load speed (1st gear / 2nd gear)	0 - 480 / 0 - 2,100 rpm
Battery type	Lithium-lon
Max. impact rate	31,500 bpm
Chuck capacity, min./max.	1.5 / 13 mm
Battery voltage	18.0 V
Weight excl. battery	1.9 kg
Torque settings	25+2
Packaging dimensions (width x length x height)	360 x 442 x 155 mm

Noise/vibration information

Drilling in metal

Vibration emission value ah	2.5 m/s ²
Uncertainty K	1.5 m/s ²
Impact drilling in masonry	
Vibration emission value ah	15.5 m/s ²
Uncertainty K	1.5 m/s ²

Invented for life

Product data sheet

Power tools for trade & industry

Advantages:

- 110 Nm maximum torque and brushless motor make the tool extremely strong
- Full-metal chuck for high durability make the impact drill driver capable of handling even the toughest applications on the jobsite
- Bluetooth Connectivity option to connect directly to a smartphone for additional tool control













