



Product data sheet

Power tools for trade & industry

Cordless Combi

GSB 18V-150 C



When strength counts – the clever impact drill driver for unrivalled power and control

The most important data

Torque (soft/hard/max.)	84/100/150 Nm
No-load speed (1st gear / 2nd gear)	0 – 550 / 0 – 2,200 rpm
Battery voltage	18.0 V

Part Number 0 601 9J5 101

Technical data

Technical data

Torque (soft/hard/max.)	84/100/150 Nm
No-load speed (1st gear / 2nd gear)	0 – 550 / 0 – 2,200 rpm
Battery type	Lithium-Ion
Max. impact rate	30,000 bpm
Chuck capacity, min./max.	1.5 / 13 mm
Battery voltage	18.0 V
Weight excl. battery	2.2 kg
Torque settings	25+2
Packaging dimensions (width x length x height)	306 x 405 x 99 mm

Noise/vibration information

Drilling in metal

Vibration emission value ah	2.5 m/s ²
Uncertainty K	1.5 m/s ²

Impact drilling in masonry

Vibration emission value ah	9.5 m/s ²
Uncertainty K	1.5 m/s ²

**BOSCH**

Invented for life

Product data sheet

Power tools for trade & industry

Advantages:

- Extremely fast work progress through a powerful brushless motor with a maximum torque of 150 Nm
- Precise Electronic Angle Detection and switchable KickBack Control enable unrivalled control at each work stage
- Reliable and robust thanks to metal drill chuck and metal gearbox

**BITURBO**
BRUSHLESS**AMP** *Share!*
BOSCH