
Product data sheet





Cordless Angle Grinder BITURBO with X-LOCK

GWX 18V-15 P



BITURBO brushless angle grinder with PROtection switch and X-LOCK – equal to 1,500 W corded power

The most important data

Battery voltage	18.0 V
Speed output no-load, nominal max.	11,000 rpm
Disc diameter	125 mm

Part Number 0 601 9H6 F00

Technical data

Technical data

Disc diameter	125 mm
Packaging dimensions (width x length x height)	160 x 381 x 154 mm
Speed output no-load, nominal max.	11,000 rpm
No-load speed	9,800 rpm
Battery voltage	18.0 V
Weight excl. battery	2.3 kg

Noise/vibration information

Surface grinding (roughing)

Vibration emission value ah	4.8 m/s ²
Uncertainty K	1.5 m/s²
Sanding with sanding sheet	
Vibration emission value ah	2.5 m/s ²
Uncertainty K	1.5 m/s ²

Invented for life

Product data sheet

Power tools for trade & industry

Advantages:

- Powerful BITURBO brushless technology delivers cordless performance equal to 1,500 W corded power
- X-brake immediately brings the disc to a standstill so you can store your tool with peace-of-mind
- PROtection switch, X-LOCK, KickBack Control, Drop Control, soft start, and Vibration Control



















