



Product data sheet

Power tools for trade & industry

Cordless Angle Grinder BITURBO with X-LOCK

GWX 18V-15 PSC



BITURBO Brushless angle grinder with PROtection switch, speed selection, and X-LOCK

The most important data

Battery voltage	18.0 V
Speed output no-load, nominal max.	11,000 rpm
Disc diameter	125 mm

Part Number 0 601 9H6 G00

Technical data

Technical data

Disc diameter	125 mm
Packaging dimensions (width x length x height)	162 x 381 x 156 mm
Speed output no-load, nominal max.	11,000 rpm
No-load speed	3,400 – 9,800 rpm
Battery voltage	18.0 V
Weight excl. battery	2.3 kg

Noise/vibration information

Surface grinding (roughing)

Vibration emission value ah	4.8 m/s ²
Uncertainty K	1.5 m/s ²

Sanding with sanding sheet

Vibration emission value ah	2.5 m/s ²
Uncertainty K	1.5 m/s ²

**BOSCH**

Invented for life

Product data sheet

Power tools for trade & industry

Advantages:

- Powerful BITURBO brushless technology delivers cordless performance equal to 1,500 W corded power
- 3 speed levels per default, retrofittable Bluetooth module for up to 6 individual speed settings
- PROtection switch, super-fast X-brake, X-LOCK, KickBack Control, Drop Control, soft start and Vibration Control

