

18V ROTARY HAMMERS



BITURBO
BRUSHLESS

CORDED POWER – WITH JUST ONE 18V BATTERY.



PRODUCT INFO

	GBH 18V-21	GBH 18V-24 C	GBH 18V-26 D	GBH 18V-26	GBH 18V-26 F	GBH 18V-28 DC	GBH 18V-34 CF	GBH 18V-36 C	GBH 18V-40 C	GBH 18V-45 C
Max. impact energy	2.0 J	2.4 J	2.5 J	2.6 J	2.6 J	3.4 J	5.8 J	7.0 J	9.0 J	12.5 J
Tool holder	SDS plus	SDS plus	SDS plus	SDS plus	SDS plus	SDS plus	SDS plus	SDS max	SDS max	SDS max
Impact rate at rated speed	0–5,100 min ⁻¹ /bpm	0–4,350 min ⁻¹ /bpm	0–4,350 min ⁻¹ /bpm	0–4,350 min ⁻¹ /bpm	0–4,350 min ⁻¹ /bpm	0–4,250 min ⁻¹ /bpm	0–2,900 min ⁻¹ /bpm	0–2,900 min ⁻¹ /bpm	0–3,130 min ⁻¹ /bpm	0–2,740 min ⁻¹ /bpm
Rated speed	0–1,800 min ⁻¹ /rpm	0–980 min ⁻¹ /rpm	0–980 min ⁻¹ /rpm	0–980 min ⁻¹ /rpm	0–980 min ⁻¹ /rpm	0–950 min ⁻¹ /rpm	0–500 min ⁻¹ /rpm	0–500 min ⁻¹ /rpm	0–360 min ⁻¹ /rpm	0–300 min ⁻¹ /rpm
Vibration drilling	15.5 m/s ²	15.5 m/s ²	16.7 m/s ²	15.2 m/s ²	15.2 m/s ²	10.1 m/s ²	10.9 m/s ²	11.4 m/s ²	7.5 m/s ²	12.3 m/s ²
Vibration chiseling	12.7 m/s ²	9.5 m/s ²	10.9 m/s ²	9.9 m/s ²	9.6 m/s ²	7.2 m/s ²	11.7 m/s ²	10.8 m/s ²	7.0 m/s ²	7.3 m/s ²
Max. drilling diameter in concrete	21 mm	24 mm	26 mm	26 mm	26 mm	28 mm	32 mm	35 mm	40 mm	45 mm
Recommended drilling range	6–10 mm	6–14 mm	8–16 mm	8–16 mm	8–16 mm	8–16 mm	12–30 mm	14–32 mm	18–32 mm	20–40 mm
Weight (excl. battery)	2.4 kg	2.9 kg	2.6 kg	3.2 kg	3.3 kg	3.0 kg	4.9 kg	5.1 kg	7.0 kg	8.0 kg

FEATURES

Brushless Motor	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
KickBack Control		✓	✓	✓	✓	✓	✓	✓	✓	✓
Rotation Control Clutch	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Vibration Control		✓		✓	✓	✓	✓	✓	✓	✓
Soft Start Drilling				✓	✓		✓	✓	✓	✓
Soft Start Chiseling							✓	✓	✓	✓
Variable Speed	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
LED Light	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Chisel Function	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Lock-on Button							✓	✓	✓	✓
Connected		✓					✓	✓		✓
Connected-Ready						✓ ¹			✓ ¹	
User Interface		✓					✓	✓	✓	✓
Individual Speed Setting		✓					✓	✓	✓	✓
Integrated Dust Extraction Ready		GDE 18V-16	GDE 18V-26D	GDE 18V-16	GDE 18V-16	GDE 28 D				
Dust Extraction Compatibility	GDE 16 Plus, GDE 68	GDE 16 Plus, GDE 68	GDE 16 Plus, GDE 68	GDE 16 Plus, GDE 68	GDE 16 Plus, GDE 68	GDE 16 Plus, GDE 68	GDE 68, GDE 162, GDE max	GDE 68, GDE 162, GDE max	GDE 68, GDE 162, GDE max	GDE 68, GDE 162, GDE max

MATERIAL

Concrete / Masonry	●	●	●	●	●	●	●	●	●	●
Wood / Steel							●	●		

RECOMMENDED BATTERIES

COMPATIBLE SINCE 2008: All of our batteries are compatible with new and existing Bosch Professional tools in the same voltage class.

GBA 18V The conventional battery for standard applications.

4.0 Ah 0.61 kg	●	●	●	●	●	●				
5.0 Ah 0.64 kg										

ProCORE18V All the power of a conventional battery – but without the weight.

4.0 Ah 0.57 kg	●	●	●	●	●	●				
-------------------	---	---	---	---	---	---	--	--	--	--

ProCORE18V The perfect balance of weight and power.

5.5 Ah 1.0 kg		●	●	●	●	●	●	●	●	●
8.0 Ah 1.0 kg										

ProCORE18V Maximum performance and longest runtime.

12.0 Ah 1.4 kg							●	●	●	●
-------------------	--	--	--	--	--	--	---	---	---	---

✓ Available functions ● Ideal for this tool

¹ The Connectivity Bluetooth module GCY 42 is not included in the scope of supply and can be purchased separately.

Values can vary depending upon the tool and are subject to application and environmental conditions. For further information www.bosch-professional.com/wac

Our most powerful batteries ever, the ProCORE18V unleashes the full power of your cordless tools.



To experience the maximum power of BITURBO tools, use ProCORE18V 5.5Ah, 8.0Ah or 12.0Ah batteries.