## **18V IMPACT DRIVERS/WRENCHES**















GDR Impact Driver GDX Impact Driver/Wrench

	GDR 18V-160	GDR 18V-200	GDR 18V-210 C	GDX 18V-200	GDX 18V-210 C
Tool holder	1/4'' Hex	1/4'' Hex	1/4'' Hex	1/4'' Hex, 1/2'' Square	1/4" Hex, 1/2" Square, friction ring+thru hole
Tigthening torque (max.)	160 Nm	200 Nm	210 Nm	200 Nm	210 Nm
<b>Torque adjustment range</b> (min./max., 1 <sup>st</sup> level)	_	-	0/80 Nm	_	0/130 Nm
<b>Torque adjustment range</b> (min./max., 2 <sup>nd</sup> level)	-	-	0/160 Nm	-	0/160 Nm
<b>Torque adjustment range</b> (min./max., 3 <sup>rd</sup> level)	-	-	0/210 Nm	-	0/210 Nm
Breakaway torque (max.)	-	-	-	350 Nm	370 Nm
Speed settings	-	-	3	-	3
No-load speed	0-2,800 min <sup>-1</sup> /rpm	0-3,400 min <sup>-1</sup> /rpm	0-1,100/2,300/ 3,400 min <sup>-1</sup> /rpm	0-3,400 min <sup>-1</sup> /rpm	0-1,100/2,300/ 3,400 min <sup>-1</sup> /rpm
mpact rate	0-3,600 min <sup>-1</sup> /bpm	0-4,000 min <sup>-1</sup> /bpm	0-2,200/3,400/ 4,000 min <sup>-1</sup> /bpm	0-4,200 min <sup>-1</sup> /bpm	0-2,200/3,400/ 4,200 min <sup>-1</sup> /bpm
Screw diameter	M6 - M14	M6 - M16	M6 - M16	M6 - M16	M6 - M16
Tool dimensions (LxWxH)	153x76x234 mm	126x61x206 mm	126x61x205 mm	147x61x206 mm	147x61x205 mm
Weight (excl. battery)	1.0 kg	1.1 kg	1.1 kg	1.1 kg	1.2 kg
Brushless Motor		~	~	~	~
Connected-Ready			✓ 1		✓ 1
Individual Speed Setting			~		~
Pre-defined screw modes on A + B			~		~
ABR					~
LED Light	~	~	~	~	~

## **COMPATIBLE SINCE 2008:** All of our batteries are compatible with new and existing Bosch Professional tools in the same voltage class.

<b>4.0 Ah</b> 0.61 kg	•	•	•	•	•
<b>5.0 Ah</b> 0.64 kg	•	٠	٠	٠	•
ProCORE18V All the power of	of a conventional battery – bu	It without the weight.			
<b>4.0Ah</b> 0.57 kg	٠	٠	٠	٠	٠
ProCORE18V The perfect ba	alance of weight and power.				
<b>5.5 Ah</b> 1.0 kg					
<b>8.0 Ah</b> 1.0 kg					

Our most powerful batteries ever, the ProCORE18V unleashes the full power of your cordless tools.



**PRODUCT INFO** 

<sup>1</sup> Depending on the order number, the Connectivity Bluetooth module GCY 42 is either included in the scope of supply or can be purchased separately.

Values can vary depending upon the tool and are subject to application and environmental conditions. For further information www.bosch-professional.com/wac