

18V RECIPROCATING SAWS



BITURBO
BRUSHLESS

CORDED POWER – WITH JUST ONE 18V BATTERY.



PRODUCT INFO

| | GSA 18 V-LI C | GSA 18 V-LI | GSA 18V-32 | GSA 18V-28 |
|--|--------------------------------|--------------------------------|--------------------------------|-------------------------------|
| Stroke length | 21 mm | 28 mm | 32 mm | 28 mm |
| Stroke rate | 0–3,050 min ⁻¹ /rpm | 0–2,700 min ⁻¹ /rpm | 0–2,500 min ⁻¹ /rpm | 0–2900 min ⁻¹ /rpm |
| Max. cutting depth in wood, metal profiles and pipes | 200/100 mm | 250/130 mm | 230/175 mm | 230/150 mm |
| Weight (excl. battery) | 2.0 kg | 2.9 kg | 3.5 kg | 3.2 kg |
| Tool dimensions without battery (LxWxH) | 367x78x177 mm | 454x71x165 mm | 482x101x198 mm | 450x96x170 mm |

FEATURES

| | | | | | |
|--|-------------------|---|---|---|---|
| | Pendulum Stroke | | | ✓ | ✓ |
| | Vibration Control | | | ✓ | |
| | Brushless Motor | | | ✓ | ✓ |
| | Toolless | ✓ | ✓ | ✓ | ✓ |
| | Speed Selection | | ✓ | ✓ | |
| | Variable Speed | ✓ | | ✓ | ✓ |
| | Rafter Hook | | | ✓ | ✓ |
| | LED Light | ✓ | | ✓ | |

MATERIAL

| | | | | |
|--|---|---|---|---|
| Wood | ● | ● | ● | ● |
| Plastic / Drywall / Insulation materials | ● | ● | ● | ● |
| Masonry / Bricks | ● | ● | ● | ● |
| Common metal (Copper, Aluminum, Steel pipes, etc.) | ● | ● | ● | ● |
| Gray cast iron pipes | | ● | ● | ● |
| Steel beams | | | | ● |

RECOMMENDED BATTERIES

COMPATIBLE

SINCE 2008: All of our batteries are compatible with new and existing Bosch Professional tools in the same voltage class.

| | | | | |
|---|---|---|---|---|
| GBA 18V The conventional battery for standard applications. | | | | |
| 4.0Ah 0.61 kg | ● | ● | ● | |
| 5.0Ah 0.64 kg | ● | ● | ● | |
| ProCORE18V All the power of a conventional battery – but without the weight. | | | | |
| 4.0Ah 0.57 kg | ● | ● | ● | |
| ProCORE18V The perfect balance of weight and power. | | | | |
| 5.5Ah 1.0 kg | | ● | ● | ● |
| 8.0Ah 1.0 kg | | ● | ● | ● |

Our most powerful batteries ever, the ProCORE18V unleashes the full power of your cordless tools.



To experience the maximum power of BITURBO tools, use ProCORE18V 5.5Ah or 8.0Ah batteries.

✓ Available functions ● Ideal for this tool

Values can vary depending upon the tool and are subject to application and environmental conditions. For further information www.bosch-professional.com/wac