













1.0 Kg	
8.0 Ah	
1.0 kg	











	GWS 18V-15 C	GWS 18V-15 SC	GWX 18V-15 SC	GWS 18V-15 P	GWX 18V-15 P	GWS 18V- 15 PSC	GWX 18V- 15 PSC	GWS 18V- 180 PC
omparable corded power	1500 W	1500 W	1500 W 1500 W		1500 W	1500 W	1500 W	1500 W
sc diameter	125 mm	125 mm	125 mm	125 mm	125 mm	125 mm	125 mm	180 mm
-load speed	9,800 min ⁻¹ /rpm	3,400 - 9,800 min ⁻¹ /rpm	3,400 - 9,800 min ⁻¹ /rpm	9,800 min ⁻¹ /rpm	9,800 min ⁻¹ /rpm	3,400 - 9,800 min ⁻¹ /rpm	3,400 - 9,800 min ⁻¹ /rpm	7,000 min ⁻¹ /rpm
inding spindle thread	M14	M14	X-LOCK	M14	X-LOCK	M14	X-LOCK	M14
eight (excl. battery)	2.2 kg	2.3 kg	2.3 kg	2.2 kg	2.3 kg	2.3 kg	2.3 kg	2.8 kg
bration emission value ah surface grinding)	1.5 m/s ²	4.0 m/s ²	6.0 m/s ²	4.9 m/s ²	4.8 m/s ²	4.9 m/s ²	4.8 m/s ²	4.1 m/s ²
bration emission value ah anding with sanding sheet)	1.5 m/s²	1.5 m/s²	2.5 m/s²	<2.5 m/s²	<2.5 m/s ²	<2.5 m/s²	<2.5 m/s²	<2.5 m/s²
DCK X-LOCK			~		~		~	
Brushless Motor	~	~	~			~	~	
KickBack Control	~	~	~	· · · · · · · · · · · · · · · · · · ·		~	~	
Drop Control	~	~	~	~	~	~	~	~
Speed Selection		~	~			~	~	
Individual Speed Setting		~	~			~	~	
Intelligent Brake System	~	~		~		~		~
X-Brake			~		~		~	
Connected		~	~			~	~	~
Connected-Ready	✓ ¹							
User Interface		~	~			~	~	
PROtection Switch				~	~	~	~	~
COMPATIBLE SINCE 2008: All of o	ur batteries are compatible v	vith new and existing Bosch Pr	rofessional tools in the same v	oltage class.				
BA 18V The conventional battery for star	ndard applications.							
4.0 Ah 0.61 kg 5.0 Ah								
0.64 kg	and bottomy but with out the weigh	•						
oCORE18V All the power of a convention 4.0 Ah 0.57 kg	iat battery – but without the Weight							
CORE18V The perfect balance of weig	ht and power.							
5.5 Ah 1.0 kg	•	•	•	•	•	•	•	•
8.0 Ah 1.0 kg	•	•	•	•	•	•	•	•

Our most powerful batteries ever, the ProCORE18V unleashes the full power of your cordless tools.



To experience the maximum power of BITURBO tools, use ProCORE18V 5.5 Ah or 8.0 Ah batteries.

18V ANGLE GRINDERS





















	GWS 18V-7	GWX 18V-7	GWS 18V-10	GWX 18V-10	GWS 18V-10 SC	GWX 18V-10 SC	GWS 18V-10 PC	GWX 18V-10 PC	GWS 18V-10 PSC	GWX 18V-10 PSC
Comparable corded power	700 W	700 W	1000 W	1000 W	1000 W	1000 W	1000 W	1000 W	1000 W	1000 W
Disc diameter	115/125 mm	115/125 mm	115/125 mm	125 mm	125 mm	125 mm	125 mm	125 mm	125 mm	125 mm
No-load speed	11,000 min ⁻¹ /rpm	11,000 min ⁻¹ /rpm	9,000 min ⁻¹ /rpm	9,000 min ⁻¹ /rpm	4,500 - 9,000 min ⁻¹ /rpm	4,500 - 9,000 min ⁻¹ /rpm	9,000 min ⁻¹ /rpm	9,000 min ⁻¹ /rpm	4,500 - 9,000 min ⁻¹ /rpm	4,500 - 9,000 min ⁻¹ /rp
Grinding spindle thread	M14	X-LOCK	M14	X-LOCK	M14	X-LOCK	M14	X-LOCK	M14	X-LOCK
Weight (excl. battery)	1.6 kg	1.6 kg	2.1 kg	2.0 kg	2.0 kg	2.0 kg	2.0 kg	2.0 kg	2.0 kg	2.0 kg
Vibration emission value ah (Surface grinding)	7.0 m/s ²	7.5 m/s ²	6.7 m/s ²	6.0 m/s ²	6.0 m/s ²	6.0 m/s ²	5.0 m/s ²	5.0 m/s ²	5.0 m/s ²	5.0 m/s ²
Vibration emission value ah (Sanding with sanding sheet)	3.5 m/s²	2.5 m/s ²	1.9 m/s ²	3.5 m/s ²	3.5 m/s ²	3.5 m/s ²	3.5 m/s ²	3.5 m/s ²	3.5 m/s ²	3.5 m/s ²
X rock X-FOCK		~		~		~		~		~
Brushless Motor	~	~	~	~	~	~	~	~	~	~
(NOCREC) KickBack Control			~	~	~	~	~	~	~	~
Drop Control			~	~	~	~	~	~	~	~
Speed Selection					~	~			~	~
Individual Speed Setting										
Intelligent Brake System			~		~		~		~	
X-Brake				~		~		~		~
Connected					~	~			~	~
Connected-Ready							✓¹	✓¹		
User Interface					~	~			~	~
PROtection Switch							~	~	~	~
COMPATIBLE SINCE 2008: All of	our batteries are compati	ble with new and existin	ng Bosch Professional t	ools in the same volta	ge class.					
GBA 18V The conventional battery for st	tandard applications.									
4.0 Ah 0.61 kg	•	•								
5.0 Ah 0.64 kg	•	•	•	•	•	•	•	•	•	•
ProCORE18V All the power of a convent	ional battery – but without the v	weight.								
4.0 Ah 0.57 kg	•	•								
ProCORE18V The perfect balance of we	eight and power.									
5.5 Ah			•	•	•	•	•	•	•	•
1.0 kg			•	•	•	•	-	•	•	•

Our most powerful batteries ever, the ProCORE18V unleashes the full power of your cordless tools.



8.0 Ah 1.0 kg